

(Apply to)

3.6V/3.7V Li-ion/IMR/INR/ICR

14650/17670/18650/18700/20700/21700

Note: Can only charge unprotected 20700/21700 batteries in single slot.



(Simple and Fast, Made for Vapers)

Max 2A for one slot, charge 18650 2500mAh battery within 1.5hrs.



(Unique Owl-Like UI Design)

Characteristic industry design with LED

indicator, both artistic and practical.

(0V Activation Function)

Most batteries we discarded for their no longer been charged are not died. Actually, it is because that their voltage are too low. And XTAR Chargers can revive and charge these low voltage batteries which other chargers can't charge.





(Current Buffering Technology)

Airplanes need smoothly accelerate (or decelerate) to take off (or land), so does the battery. Current Buffering Technology keeps batteries from violent currents.

(Elaborate Heat Dissipation Design)

Keep the temperature impressively low during fast charging with 2A.



[Battery Life Optimization Charging]

People need a healthy diet, so does the battery. TC/CC/CV three-stage charging method like the three courses of a meal. First we have some soup or salad as an appetizer (TC), then eat the main course to get full (CC), finally we have some dessert to get real full and happy (CV). Then the battery can work for you enduringly.



(Specifications)

Model	D2
Input	100-240V~ 50/60Hz 0.4A
Constant Current	2A×1 / 1A×2
Cut-Off Voltage	4.20 ± 0.05V
Operating Temperature	0-40°C
Size	L130*W58*H33mm
Net weight	103g

(Safe, Durable and Peace of Mind)

ROHS FC CE





Short-circuit Protection



over heat protection



Over-current Protection



Over-charge Protection



material



Protection



1 year warranty



Temperature monitoring design

(Package)

D2 Charger, Power Cord, Manual

