# **Emergency consumer units**

# Livorno Series flush and wall-mounting consumer units

# 100x100x50 mm

# 200x245x82 mm

# 200x245x82 mm

# Flush-mounting version

IP 55

RAL 3000 red

Possibility of installing on flush-mounting enclosure with inter-axis of 83.5 mm. With luminous button (E10-12/24V incandescence and 220V fluorescence), with 1 NO contact + 1 NC contact (2A, 250 V) complete with glass-breaking hammer



No. items Box/pack
1/13

IP 40 RAL 3000 red



Article	D <b>escri</b> ption	N <b>o. items</b> B <b>ox</b> /pa <b>c</b> k
13 144	w <b>it</b> h DIN	<b>1</b> /7
	x 6 mod. guide	
13 154	w <b>it</b> h pa <b>ne</b> l	<b>1</b> /7

IP 40 RAL 7035 grey



A <b>rtic</b> le	D <b>escri</b> ption	No. items Box/pack
13 143	w <b>it</b> h DIN	<b>1</b> /7
	x 6 mod. guide	
13 153	w <b>it</b> h pa <b>ne</b> l	<b>1</b> /7

Glass-breaking hammer

13 186 1/10

# 100x100x50 mm

### 205x220x140 mm

### 205x220x140 mm

# 165x180x110 mm

### Wall-mounting version

IP 55

RAL 3000 red

With luminous button (E10-12/24V incandescence and 220V fluorescence), with 1 NO contact + 1 NC contact (2A, 250 V) complete with glass-breaking hammer

IP 65

RAL 3000 red

Fitted with flanges for facilitated branch connections

IP 65

RAL 7035 grey Fitted with flanges for facilitated

branch connections

IP 55

RAL 3000 red





Article	D <b>escri</b> ption	No. items Box/pack
<b>13 1</b> 71	w <b>it</b> h DIN	1/6
	x 6 mod. guide	
<b>13 1</b> 7 <b>5</b>	w <b>it</b> h pa <b>ne</b> l	1/6



A <b>rticle</b>	D <b>escri</b> ption	No. items Box/pack
<b>13 1</b> 7 <b>0</b>	with DIN	1/6
	x 6 mod. guide	
<b>13 1</b> 74	w <b>it</b> h pa <b>ne</b> l	1/6



Article	Description	No. items Box/pack
13 161	with DIN x 6 mod. quide	1/12
13 165		1/12

3/4 ABB SACE