

tesaflex® 4252

PVC Electrical Insulation Tape

PRODUCT INFORMATION

Product Description

tesaflex® 4252 is an economical grade plasticized PVC tape with good flexibility and electrical properties.

Having a modified rubber resin adhesive coating, tesaflex® 4252 provides good adhesion and ageing resistance in most applications.

Main Application

tesaflex® 4252 is suitable for most electrical insulation applications such as splicing and protection.

The assorted colour range of tesaflex® 4252 makes it useful in decorative and colour coding applications as well.

Technical Data

- soft PVC Backing material Adhesion to steel 1.7 N/cm Total thickness 120 µm Elongation at break 100 %
- Type of adhesive natural rubber Tensile strength 13 N/cm

Properties

Certified according to none

For latest information on this product please visit http://l.tesa.com/?ip=04252

Page 1 of 1 / As of 07/28/13

tesa SE

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Phone: +1 (704) 554 0707 Phone: +65 (68) 612 026

tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle, Singapore 629621

Fax: +1 (704) 553 5634 Fax: +65 (68) 614 790 http://www.tesatape.com http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.