

LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Type K, Mineral Insulated thermocouple



Specifications

- Sensor Type Thermocouple type K to IEC 60584
- Probe Material 310 stainless steel with welded tip. Mineral insulated
- conductors with insulated junction
- Tip Temperature Rating -40°C to 1100°C
- Probe termination Plain pot seal
- Pot temperature Rating 180°C
- Termination Flying lead & tails; PTFE insulated, 7/0.2mm, 1 metre

Туре	Dia	Probe	Cable	Manufacturer Part No	Farnell
		Length	Length		Order #
	(mm)	(mm)	(mtrs)		
K	1.5	150	1	XF-329-FAR	424-8193
K	1.5	250	1	XF-330-FAR	424-8200
K	3	150	1	XF-331-FAR	424-8211
K	3	250	1	XF-332-FAR	424-8223
K	6	150	1	XF-333-FAR	424-8235
K	6	250	1	XF-334-FAR	424-8247

About Labfacility

Formed in 1971, Labfacility specialize in the field of Temperature and Process Measurement.

We are the largest UK manufacturer of both temperature sensors and thermocouple connectors

Quality & Service

Quality and Service are key elements in the continued growth of Labfacility.

Technical support is always freely available from our experienced technical sales teams and the company has ISO9001 accreditation.

Contact Details

Email sales@labfacility.com

Website www.labfacility.com