

TP1000EC Series (90W~180W)

Introduction

The TP1000EC series are low-cost linear DC power supplies with 1 channels, 90W to 180W output. In constant voltage and current operations, the power supply provides high regulation and low ripple & noise. There is coarse and fine control adjustment for voltage and current. The TP1000EC series are widely used in applications of powering operational amplifier, push pull stages, logic circuit and definition systems.

Features

- ✓ Constant voltage and constant current operations
- ✓ High efficiency, light and compact design
- ✓ High power density
- ✓ Over load and reverse polarity protections
- ✓ Dual-color two digital panel meters

Product photo



TP-1303EC

Single Output Linear DC Power Supply



Specifications

| Model | TP-1303EC | TP-1305EC | TP-1603EC |
|-----------------------------------|----------------------|--|------------|
| Output | 0~30V/0~3A | 0~30V/0~5A | 0~60V/0~3A |
| Constant voltage operation | | | |
| Line regulation | ≤0.01%+3mV | | |
| Load regulation | ≤0.01%+3mV | ≤0.02%+5mV | ≤0.01%+3mV |
| Ripple & Noise | ≤2mVrms | | |
| Constant current operation | | | |
| Line regulation | ≤0.2%+3mA | | |
| Load regulation | ≤0.2%+3mA | | |
| Display | | | |
| Voltmeter | 3 digits LED display | | |
| Ammeter | 3 digits LED display | | |
| Resolution | 100mV/10mA | | |
| Accuracy | Voltage | ±(0.5% reading+2 digits) | |
| | Current | ±(1% reading+2 digits) | |
| Protection | | Over load and reverse polarity protections | |
| Power source | | AC110V, AC220V or AC110V/220V±10%, 50/60Hz | |
| Operating environment | | 0°C~40°C, ≤80%RH | |
| Storage environment | | -10°C~70°C, ≤70%RH | |
| Accessories | | Power cord x1, Operation manual x1, Test lead x1 | |

Selection Guide

| Model | TP-1303 | TP-1305 | TP-1603 | TP-1303C | TP-1305C | TP-1603C | TP-1303EC | TP-1305EC | TP-1603EC |
|-----------------------|---------------|---------|---------|----------|----------|----------|-----------|-----------|-----------|
| Output voltage | 0~30V | 0~30V | 0~60V | 0~30V | 0~30V | 0~60V | 0~30V | 0~30V | 0~60V |
| Output current | 0~3A | 0~5A | 0~3A | 0~3A | 0~5A | 0~3A | 0~3A | 0~5A | 0~3A |
| Fixed output | 5V/1A | 5V/1A | 5V/1A | | | | | | |
| Preset V&I | | | | | | | | | |
| Output ON/OFF | √ | √ | √ | √ | √ | √ | | | |
| Dimension | 160x130x310mm | | | | | | | | |
| Weight | 5 kg | 5.5 kg | 6 kg | 5 kg | 5.5 kg | 6 kg | 4.5 kg | 5 kg | 5.5kg |