



Nr. / No.	Länge / Length (m)
51675	1.0
51679	10.0
51676	2.0
51677	3.0
51678	5.0

- WLAN Antennenverlängerungskabel
  - RP-SMA Stecker > RP-SMA Buchse
  - RG 58 LowLoss Koaxialkabel
  - vergoldete SMA Reverse Steckverbinder
  - Schirmung: doppelt  
Al-Folie + Geflecht 112\*0.1mm Cu
  - Innenleiter: Ø0.8mm Cu
  - Dielektrikum: PE Ø2.85mm
  - RoHS-konform
- WLAN antenna extension cable
  - RP-SMA plug > RP-SMA jack
  - RG 58 LowLoss coaxial cable
  - gold plated SMA Reverse connectors
  - Shielding: double  
Al Foil + Braiding 112\*0.1mm Cu
  - Inner conductor: Ø0.8mm Cu
  - Dielectric: PE Ø2.85mm
  - RoHS-compliant

### Änderungen

Datum	Name	gez.:	Datum	Name
		gef.:	27.01.2014	tf
		gepr.:	27.01.2014	tf
		Norm:		
Änderungen vorbehalten / Subject to change				

Bezeichnung	Blatt
RP-SMA FM	
	
Zeichnungs-Nr.:	von