


# Capillary Thermostats

## TS Series



RoHS  
Compliant



Without Stuffing Bolt

With Stuffing Bolt


### Applications

- Fridge, freezer, hot and cool dispenser, air conditioner.
- All sorts of cooking equipment's such as fryers, electric oven, microwave, waffle maker and so forth.


### Specifications

Capillary	: 1,000mm (250mm to 2,000mm)
Knob (Dial)	: R or B
Stuffing Bolt	: PT1/4, M12, M14
Mounting Distance	: 28mm
Electric Rating	: 20A / 250V
Switch Action	: SPST / SPDT
Shaft Range	: 270
Ambient Temp.	: 120°C
Tab Terminal	: Straight, 90°


### Diagram



#### ► Switch/Circuit Diagram



#### ► Functional Description



Dimensions : Millimetres



# Capillary Thermostats TS Series



## Option and Accessory



## Part Number Table

Description	Temperature Range	Bulb	Part Number
Capillary Thermostat, 20A, 250V AC	-30°C to +30°C	5.8mm × 127mm	TS-030S R
Capillary Thermostat, 20A, 250V AC	0°C to +40°C	5.8mm × 127mm	TS-040S R
Capillary Thermostat, 20A, 250V AC	0°C to +50°C	5.8mm × 127mm	TS-050S R
Capillary Thermostat, 20A, 250V AC	0°C to +80°C	5.8mm × 121mm	TS-080S R
Capillary Thermostat, 20A, 250V AC	0°C to +90°C	5.8mm × 120mm	TS-090S R
Capillary Thermostat, 20A, 250V AC	0°C to +120°C	5mm × 104mm	TS-120S R
Capillary Thermostat, 20A, 250V AC	30°C to +150°C	5mm × 100mm	TS-150S R
Capillary Thermostat, 20A, 250V AC	50°C to +200°C	5mm × 58mm	TS-200S R
Capillary Thermostat, 20A, 250V AC	50°C to +320°C	5mm × 58mm	TS-320S R



# Capillary Thermostats

## TS Series



Description	Temperature Range	Bulb	Part Number
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	-30°C to +30°C	5.8mm × 127mm	TS-030SR-C
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	0°C to +40°C	5.8mm × 127mm	TS-040SR-C
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	0°C to +50°C	5.8mm × 127mm	TS-050SR-C
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	0°C to +80°C	5.8mm × 121mm	TS-080SR-C
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	0°C to +90°C	5.8mm × 120mm	TS-090SR-C
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	0°C to +120°C	5mm × 104mm	TS-120SR-C
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	30°C to +150°C	5mm × 100mm	TS-150SR-C
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	50°C to +200°C	5mm × 58mm	TS-200SR-C
Capillary Thermostat, 20A, 250V AC, Stuffing Bolt	50°C to +320°C	5mm × 58mm	TS-320SR-C

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of Premier Farnell Limited 2019.

